

**AD-A247 334**

**TATION PAGE**

Form Approved  
OPM No. 0704-0188

Publ  
near  
Has  
Man



ur per response, including the time for reviewing instructions, searching existing data sources gathering and maintaining the data burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Herson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Information and Regulatory Affairs, Office of

|  |   |  |                            |   |  |
|--|---|--|----------------------------|---|--|
| 1. AGENCY USE ONLY (Leave Blank)   |   | 2. REPORT DATE   |                            | 3. REPORT TYPE AND DATES COVERED<br>Final: 12 Oct 1991 to 01 Jun 1993 |  |
| 4. TITLE AND SUBTITLE<br>Validation Summary Report: Aitech Defense Systems Inc., AI-ADA/96K, Version 3.0, Sun-4/330 under SunOS 4.1.1(Host) to DSP96002 ADS board (bare machine)(Target), 911012W1.11225   |   |  |                            | 5. FUNDING NUMBERS  |  |
| 6. AUTHOR(S)<br>Wright-Patterson AFB, Dayton, OH<br>USA  |   |  |                            |   |  |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)<br>Ada Validation Facility, Language Control Facility ASD/SCEL<br>Bldg. 676, Rm 135<br>Wright-Patterson AFB, Dayton, OH 45433                           |   |  |                            | 8. PERFORMING ORGANIZATION<br>REPORT NUMBER<br>AVF-VSR-507.0292       |  |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)<br>Ada Joint Program Office<br>United States Department of Defense<br>Pentagon, Rm 3E114<br>Washington, D.C. 20301-3081                            |   |  |                            | 10. SPONSORING/MONITORING AGENCY<br>REPORT NUMBER                     |  |
| 11. SUPPLEMENTARY NOTES  |   |  |                            |   |  |
| 12a. DISTRIBUTION/AVAILABILITY STATEMENT<br>Approved for public release; distribution unlimited.   |   |  |                            | 12b. DISTRIBUTION CODE  |  |
| 13. ABSTRACT (Maximum 200 words)<br>Aitech Defense Systems Inc., AI-ADA/96K, Version 3.0, Wright-Patterson AFB, Sun-4/330 under SunOS 4.1.1(Host) to DSP96002 ADS board (bare machine)(Target), ACVC 1.11. |   |  |                            |   |  |
| 14. SUBJECT TERMS<br>Ada programming language, Ada Compiler Val. Summary Report, Ada Compiler Val. Capability, Val. Testing, Ada Val. Office, Ada Val. Facility, ANSI/MIL-STD-1815A, AJPO.                 |   |  |                            | 15. NUMBER OF PAGES   |  |
|  |   |  |                            | 16. PRICE CODE  |  |
| 17. SECURITY CLASSIFICATION<br>OF REPORT<br>UNCLASSIFIED   | 18. SECURITY CLASSIFICATION<br>UNCLASSIFIED | 19. SECURITY CLASSIFICATION<br>OF ABSTRACT<br>UNCLASSIFIED | 20. LIMITATION OF ABSTRACT |   |  |

**DTIC**  
**ELECTE**  
**S MAR 10 1992 D**  
**C**

AVF Control Number: AVF-VSR-507.0292  
4 February 1992  
91-06-21-AIT

Ada COMPILER  
VALIDATION SUMMARY REPORT:  
Certificate Number: 911012W1.11225  
Aitech Defense Systems Inc.  
AI-ADA/96K, Version 3.0  
Sun-4/330 under SunOS 4.1.1 => DSP96002 ADS board (bare machine)

Prepared By:  
Ada Validation Facility  
ASD/SCEL  
Wright-Patterson AFB OH 45433-6503

|                    |  |
|--------------------|--|
| Accession For      |  |
| NTIS GRA&I         | <input checked="checked" type="checkbox"/> |
| DTIC TAB           | <input type="checkbox"/>                   |
| Unannounced        | <input type="checkbox"/>                   |
| Justification      |  |
| By                 |  |
| Distribution/      |  |
| Availability Codes |  |
| Dist               | Avail and/or<br>Special                    |
| A-1                |  |



92 3 05 013

92-05963



## Certificate Information

The following Ada implementation was tested and determined to pass ACVC 1.11. Testing was completed on 12 October 1991.

Compiler Name and Version: AI-ADA/96K, Version 3.0

Host Computer System: Sun-4/330 under SunOS 4.1.1


Target Computer System: DSP96002 ADS board (bare machine)


Customer Agreement Number: 91-06-21-AIT


See section 3.1 for any additional information about the testing environment.

As a result of this validation effort, Validation Certificate 911012W1.11225 is awarded to Aitech Defense Systems Inc. This certificate expires on 1 June 1993.

This report has been reviewed and is approved.

  
\_\_\_\_\_  
Ada Validation Facility  
Steven P. Wilson  
Technical Director  
ASD/SCEL  
Wright-Patterson AFB OH 45433-6503

  
\_\_\_\_\_  
Ada Validation Organization  
Director, Computer and Software Engineering Division  
Institute for Defense Analyses  
Alexandria VA 22311

  
\_\_\_\_\_  
Ada Joint Program Office  
Dr. John Solomond, Director  
Department of Defense  
Washington DC 20301



## **DECLARATION OF CONFORMANCE**

**Customer:** AITECH Defense Systems Inc.

**Ada Validation Facility:** ASD/SCEL, Wright-Patterson AFB

**ACVC Version** 1.11

**Ada Implementation:**


**Compiler Name and Version:** AI-ADA/96K Version 3.0

**Host Computer System:** Sun-4/330 SunOS 4.1.1

**Target Computer System:** DSP96002 ADS Board Bare Machine

### **Customer's Declaration**

*I, the undersigned, representing AITECH Defense Systems, declare that AITECH Defense Systems has no knowledge of deliberate deviations from Ada Language Standard ANSI/MIL-STD-1815A in the implementation listed in this declaration.*

  
Gabriel Leemor  
AITECH Defense Systems Inc.  
3080 Olcott St., Suite 105A  
Santa Clara, CA 95054

## TABLE OF CONTENTS

|            |   |     |
|------------|---|-----|
| CHAPTER 1  | INTRODUCTION                                    |     |
| 1.1        | USE OF THIS VALIDATION SUMMARY REPORT . . . . . | 1-1 |
| 1.2        | REFERENCES. . . . .                             | 1-2 |
| 1.3        | ACVC TEST CLASSES . . . . .                     | 1-2 |
| 1.4        | DEFINITION OF TERMS . . . . .                   | 1-3 |
| CHAPTER 2  | IMPLEMENTATION DEPENDENCIES                     |     |
| 2.1        | WITHDRAWN TESTS . . . . .                       | 2-1 |
| 2.2        | INAPPLICABLE TESTS. . . . .                     | 2-1 |
| 2.3        | TEST MODIFICATIONS. . . . .                     | 2-4 |
| CHAPTER 3  | PROCESSING INFORMATION                          |     |
| 3.1        | TESTING ENVIRONMENT . . . . .                   | 3-1 |
| 3.2        | SUMMARY OF TEST RESULTS . . . . .               | 3-1 |
| 3.3        | TEST EXECUTION. . . . .                         | 3-2 |
| APPENDIX A | MACRO PARAMETERS                                |     |
| APPENDIX B | COMPILATION SYSTEM OPTIONS                      |     |
| APPENDIX C | APPENDIX F OF THE Ada STANDARD                  |     |

## CHAPTER 1

### INTRODUCTION

The Ada implementation described above was tested according to the Ada Validation Procedures [Pro90] against the Ada Standard [Ada83] using the current Ada Compiler Validation Capability (ACVC). This Validation Summary Report (VSR) gives an account of the testing of this Ada implementation. For any technical terms used in this report, the reader is referred to [Pro90]. A detailed description of the ACVC may be found in the current ACVC User's Guide [UG89].

#### 1.1 USE OF THIS VALIDATION SUMMARY REPORT

Consistent with the national laws of the originating country, the Ada Certification Body may make full and free public disclosure of this report. In the United States, this is provided in accordance with the "Freedom of Information Act" (5 U.S.C. #552). The results of this validation apply only to the computers, operating systems, and compiler versions identified in this report.

The organizations represented on the signature page of this report do not represent or warrant that all statements set forth in this report are accurate and complete, or that the subject implementation has no nonconformities to the Ada Standard other than those presented. Copies of this report are available to the public from the AVF which performed this validation or from:

National Technical Information Service  
5285 Port Royal Road  
Springfield VA 22161

Questions regarding this report or the validation test results should be directed to the AVF which performed this validation or to:

Ada Validation Organization  
Computer and Software Engineering Division  
Institute for Defense Analyses  
1801 North Beauregard Street  
Alexandria VA 22311-1772

## INTRODUCTION

### 1.2 REFERENCES

- [Ada83] Reference Manual for the Ada Programming Language,  
ANSI/MIL-STD-1815A, February 1983 and ISO 8652-1987.
- [Pro90] Ada Compiler Validation Procedures, Version 2.1, Ada Joint  
Program Office, August 1990.
- [UG89] Ada Compiler Validation Capability User's Guide, 21 June 1989.

### 1.3 ACVC TEST CLASSES

Compliance of Ada implementations is tested by means of the ACVC. The ACVC contains a collection of test programs structured into six test classes: A, B, C, D, E, and L. The first letter of a test name identifies the class to which it belongs. Class A, C, D, and E tests are executable. Class B and class L tests are expected to produce errors at compile time and link time, respectively.

The executable tests are written in a self-checking manner and produce a PASSED, FAILED, or NOT APPLICABLE message indicating the result when they are executed. Three Ada library units, the packages REPORT and SPRT13, and the procedure CHECK\_FILE are used for this purpose. The package REPORT also provides a set of Identity functions used to defeat some compiler optimizations allowed by the Ada Standard that would circumvent a test objective. The package SPRT13 is used by many tests for Chapter 13 of the Ada Standard. The procedure CHECK\_FILE is used to check the contents of text files written by some of the Class C tests for Chapter 14 of the Ada Standard. The operation of REPORT and CHECK\_FILE is checked by a set of executable tests. If these units are not operating correctly, validation testing is discontinued.

Class B tests check that a compiler detects illegal language usage. Class B tests are not executable. Each test in this class is compiled and the resulting compilation listing is examined to verify that all violations of the Ada Standard are detected. Some of the class B tests contain legal Ada code which must not be flagged illegal by the compiler. This behavior is also verified.

Class L tests check that an Ada implementation correctly detects violation of the Ada Standard involving multiple, separately compiled units. Errors are expected at link time, and execution is attempted.

In some tests of the ACVC, certain macro strings have to be replaced by implementation-specific values — for example, the largest integer. A list of the values used for this implementation is provided in Appendix A. In addition to these anticipated test modifications, additional changes may be required to remove unforeseen conflicts between the tests and implementation-dependent characteristics. The modifications required for this implementation are described in section 2.3.

For each Ada implementation, a customized test suite is produced by the AVF. This customization consists of making the modifications described in the preceding paragraph, removing withdrawn tests (see section 2.1), and possibly removing some inapplicable tests (see section 2.2 and [UG89]).

In order to pass an ACVC an Ada implementation must process each test of the customized test suite according to the Ada Standard.

#### 1.4 DEFINITION OF TERMS

|   |   |
|---|---|
| Ada Compiler                              | The software and any needed hardware that have to be added to a given host and target computer system to allow transformation of Ada programs into executable form and execution thereof.   |
| Ada Compiler Validation Capability (ACVC) | The means for testing compliance of Ada implementations, consisting of the test suite, the support programs, the ACVC user's guide and the template for the validation summary report.  |
| Ada Implementation                        | An Ada compiler with its host computer system and its target computer system.   |
| Ada Joint Program Office (AJPO)           | The part of the certification body which provides policy and guidance for the Ada certification system.   |
| Ada Validation Facility (AVF)             | The part of the certification body which carries out the procedures required to establish the compliance of an Ada implementation.  |
| Ada Validation Organization (AVO)         | The part of the certification body that provides technical guidance for operations of the Ada certification system.   |
| Compliance of an Ada Implementation       | The ability of the implementation to pass an ACVC version.  |
| Computer System                           | A functional unit, consisting of one or more computers and associated software, that uses common storage for all or part of a program and also for all or part of the data necessary for the execution of the program; executes user-written or user-designated programs; performs user-designated data manipulation, including arithmetic operations and logic operations; and that can execute programs that modify themselves during execution. A computer system may be a stand-alone unit or may consist of several inter-connected units. |



## INTRODUCTION

|                              |   |
|------------------------------|---|
| Conformity                   | Fulfillment by a product, process, or service of all requirements specified.  |
| Customer                     | An individual or corporate entity who enters into an agreement with an AVF which specifies the terms and conditions for AVF services (of any kind) to be performed.   |
| Declaration of Conformance   | A formal statement from a customer assuring that conformity is realized or attainable on the Ada implementation for which validation status is realized.  |
| Host Computer System         | A computer system where Ada source programs are transformed into executable form.   |
| Inapplicable test            | A test that contains one or more test objectives found to be irrelevant for the given Ada implementation.   |
| ISO                          | International Organization for Standardization.   |
| LRM                          | The Ada standard, or Language Reference Manual, published as ANSI/MIL-STD-1815A-1983 and ISO 8652-1987. Citations from the LRM take the form "<section>.<subsection>:<paragraph>."  |
| Operating System             | Software that controls the execution of programs and that provides services such as resource allocation, scheduling, input/output control, and data management. Usually, operating systems are predominantly software, but partial or complete hardware implementations are possible. |
| Target Computer System       | A computer system where the executable form of Ada programs are executed.   |
| Validated Ada Compiler       | The compiler of a validated Ada implementation.   |
| Validated Ada Implementation | An Ada implementation that has been validated successfully either by AVF testing or by registration [Pro90].  |
| Validation                   | The process of checking the conformity of an Ada compiler to the Ada programming language and of issuing a certificate for this implementation.   |
| Withdrawn test               | A test found to be incorrect and not used in conformity testing. A test may be incorrect because it has an invalid test objective, fails to meet its test objective, or contains erroneous or illegal use of the Ada programming language.  |

## CHAPTER 2

### IMPLEMENTATION DEPENDENCIES

#### 2.1 WITHDRAWN TESTS

The following tests have been withdrawn by the AVO. The rationale for withdrawing each test is available from either the AVO or the AVF. The publication date for this list of withdrawn tests is 2 August 1991.

|         |         |         |         |         |         |
|---------|---------|---------|---------|---------|---------|
| E28005C | B28006C | C32203A | C34006D | C35508I | C35508J |
| C35508M | C35508N | C35702A | C35702B | B41308B | C43004A |
| C45114A | C45346A | C45612A | C45612B | C45612C | C45651A |
| C46022A | B49008A | B49008B | A74006A | C74308A | B83022B |
| B83022H | B83025B | B83025D | C83026A | B83026B | C83041A |
| B85001L | C86001F | C94021A | C97116A | C98003B | BA2011A |
| CB7001A | CB7001B | CB7004A | CC1223A | BC1226A | CC1226B |
| BC3009B | BD1B02B | BD1B06A | AD1B08A | BD2A02A | CD2A21E |
| CD2A23E | CD2A32A | CD2A41A | CD2A41E | CD2A87A | CD2B15C |
| BD3006A | BD4008A | CD4022A | CD4022D | CD4024B | CD4024C |
| CD4024D | CD4031A | CD4051D | CD5111A | CD7004C | ED7005D |
| CD7005E | AD7006A | CD7006E | AD7201A | AD7201E | CD7204B |
| AD7206A | BD8002A | BD8004C | CD9005A | CD9005B | CDA201E |
| CE2107I | CE2117A | CE2117B | CE2119B | CE2205B | CE2405A |
| CE3111C | CE3116A | CE3118A | CE3411B | CE3412B | CE3607B |
| CE3607C | CE3607D | CE3812A | CE3814A | CE3902B |         |

#### 2.2 INAPPLICABLE TESTS

A test is inapplicable if it contains test objectives which are irrelevant for a given Ada implementation. Reasons for a test's inapplicability may be supported by documents issued by the ISO and the AJPO known as Ada Commentaries and commonly referenced in the format AI-ddddd. For this implementation, the following tests were determined to be inapplicable for the reasons indicated; references to Ada Commentaries are included as appropriate.

## IMPLEMENTATION DEPENDENCIES

The following 285 tests have floating-point type declarations requiring more digits than `SYSTEM.MAX_DIGITS`:

|                       |                       |
|-----------------------|-----------------------|
| C24113F..Y (20 tests) | C35705F..Y (20 tests) |
| C35706F..Y (20 tests) | C35707F..Y (20 tests) |
| C35708F..Y (20 tests) | C35802F..Z (21 tests) |
| C45241F..Y (20 tests) | C45321F..Y (20 tests) |
| C45421F..Y (20 tests) | C45521F..Z (21 tests) |
| C45524F..Z (21 tests) | C45621F..Z (21 tests) |
| C45641F..Y (20 tests) | C46012F..Z (21 tests) |

The following 21 tests check for the predefined type `SHORT_INTEGER`; for this implementation, there is no such type:

|         |         |         |         |         |
|---------|---------|---------|---------|---------|
| C35404B | B36105C | C45231B | C45304B | C45411B |
| C45412B | C45502B | C45503B | C45504B | C45504E |
| C45611B | C45613B | C45614B | C45631B | C45632B |
| B52004E | C55B07B | B55B09D | B86001V | C86006D |
| CD7101E |         |         |         |         |

The following 20 tests check for the predefined type `LONG_INTEGER`; for this implementation, there is no such type:

|         |         |         |         |         |
|---------|---------|---------|---------|---------|
| C35404C | C45231C | C45304C | C45411C | C45412C |
| C45502C | C45503C | C45504C | C45504F | C45611C |
| C45613C | C45614C | C45631C | C45632C | B52004D |
| C55B07A | B55B09C | B86001W | C86006C | CD7101F |

C35404D, C45231D, B86001X, C86006E, and CD7101G check for a predefined integer type with a name other than `INTEGER`, `LONG_INTEGER`, or `SHORT_INTEGER`; for this implementation, there is no such type.

C35713B, C45423B, B86001T, and C86006H check for the predefined type `SHORT_FLOAT`; for this implementation, there is no such type.

C35713D and B86001Z check for a predefined floating-point type with a name other than `FLOAT`, `LONG_FLOAT`, or `SHORT_FLOAT`; for this implementation, there is no such type.

C45531M..P and C45532M..P (8 tests) check fixed-point operations for types that require a `SYSTEM.MAX_MANTISSA` of 47 or greater; for this implementation, `MAX_MANTISSA` is less than 47.

C45536A, C46013B, C46031B, C46033B, and C46034B contain length clauses that specify values for `'SMALL` that are not powers of two or ten; this implementation does not support such values for `'SMALL`.

C45624A..B (2 tests) check that the proper exception is raised if `MACHINE_OVERFLOW`s is `FALSE` for floating point types and the results of various floating-point operations lie outside the range of the base type; for this implementation, `MACHINE_OVERFLOW`s is `TRUE`.

## IMPLEMENTATION DEPENDENCIES

C4A013B contains a static universal real expression that exceeds the range of this implementation's largest floating-point type; this expression is rejected by the compiler.

B86001Y uses the name of a predefined fixed-point type other than type DURATION; for this implementation, there is no such type.

C96005B uses values of type DURATION's base type that are outside the range of type DURATION; for this implementation, the ranges are the same.

CA2009A, CA2009C..D (2 tests), CA2009F, and BC3009C instantiate generic units before their bodies are compiled; this implementation requires that the body of a generic unit be compiled before any instantiation of that unit, as allowed by AI-00506. (See Section 2.3.)

LA3004A..B, EA3004C..D, and CA3004E..F (6 tests) check pragma INLINE for procedures and functions; this implementation does not support pragma INLINE.

CD1009C checks whether a length clause can specify a non-default size for a floating-point type; this implementation does not support such sizes.

CD2A84A, CD2A84E, CD2A84I..J (2 tests), and CD2A84O use length clauses to specify non-default sizes for access types; this implementation does not support such sizes.

BD8001A, BD8003A, BD8004A..B (2 tests), and AD8011A use machine code insertions; this implementation provides no package MACHINE\_CODE.

The following 264 tests check operations on sequential, text, and direct access files; this implementation does not support external files:

|                |                |                |                 |
|----------------|----------------|----------------|-----------------|
| CE2102A..C (3) | CE2102G..H (2) | CE2102K        | CE2102N..Y (12) |
| CE2103C..D (2) | CE2104A..D (4) | CE2105A..B (2) | CE2106A..B (2)  |
| CE2107A..H (8) | CE2107L        | CE2108A..H (8) | CE2109A..C (3)  |
| CE2110A..D (4) | CE2111A..I (9) | CE2115A..B (2) | CE2120A..B (2)  |
| CE2201A..C (3) | EE2201D..E (2) | CE2201F..N (9) | CE2203A         |
| CE2204A..D (4) | CE2205A        | CE2206A        | CE2208B         |
| CE2401A..C (3) | EE2401D        | CE2401E..F (2) | EE2401G         |
| CE2401H..L (5) | CE2403A        | CE2404A..B (2) | CE2405B         |
| CE2406A        | CE2407A..B (2) | CE2408A..B (2) | CE2409A..B (2)  |
| CE2410A..B (2) | CE2411A        | CE3102A..C (3) | CE3102F..H (3)  |
| CE3102J..K (2) | CE3103A        | CE3104A..C (3) | CE3106A..B (2)  |
| CE3107B        | CE3108A..B (2) | CE3109A        | CE3110A         |
| CE3111A..B (2) | CE3111D..E (2) | CE3112A..D (4) | CE3114A..B (2)  |
| CE3115A        | CE3119A        | EE3203A        | EE3204A         |
| CE3207A        | CE3208A        | CE3301A        | EE3301B         |
| CE3302A        | CE3304A        | CE3305A        | CE3401A         |
| CE3402A        | EE3402B        | CE3402C..D (2) | CE3403A..C (3)  |

## IMPLEMENTATION DEPENDENCIES

|                |                |                 |                |
|----------------|----------------|-----------------|----------------|
| CE3403E..F (2) | CE3404B..D (3) | CE3405A         | EE3405B        |
| CE3405C..D (2) | CE3406A..D (4) | CE3407A..C (3)  | CE3408A..C (3) |
| CE3409A        | CE3409C..E (3) | EE3409F         | CE3410A        |
| CE3410C..E (3) | EE3410F        | CE3411A         | CE3411C        |
| CE3412A        | EE3412C        | CE3413A..C (3)  | CE3414A        |
| CE3602A..D (4) | CE3603A        | CE3604A..B (2)  | CE3605A..E (5) |
| CE3606A..B (2) | CE3704A..F (6) | CE3704M..O (3)  | CE3705A..E (5) |
| CE3706D        | CE3706F..G (2) | CE3804A..P (16) | CE3805A..B (2) |
| CE3806A..B (2) | CE3806D..E (2) | CE3806G..H (2)  | CE3904A..B (2) |
| CE3905A..C (3) | CE3905L        | CE3906A..C (3)  | CE3906E..F (2) |

CE2103A, CE2103B, and CE3107A use an illegal file name in an attempt to create a file and expect NAME\_ERROR to be raised; this implementation does not support external files and so raises USE\_ERROR. (See Section 2.3.)

## 2.3 TEST MODIFICATIONS

Modifications (see section 1.3) were required for 23 tests.

The following tests were split into two or more tests because this implementation did not report the violations of the Ada Standard in the way expected by the original tests.

|         |         |         |         |         |         |
|---------|---------|---------|---------|---------|---------|
| B55A01A | BA1101E | BA3006A | BA3006B | BA3007B | BA3008A |
| BA3008B | BA3013A | BC2001D | BC2001E |         |         |

CA2009A, CA2009C..D (2 tests), CA2009F, and BC3009C were graded inapplicable by Evaluation Modification as directed by the AVO. These tests instantiate generic units before those units' bodies are compiled; this implementation rejects a unit that contains an instantiation of a unit whose body is not in the program library.

BC3204C..D (2 tests) and BC3205C..D (2 tests) were graded passed by Processing Modification as directed by the AVO. These tests check that instantiations of generic units with unconstrained types as generic actual parameters are illegal if the generic bodies contain uses of the types that require a constraint. However, the generic bodies are compiled after the units that contain the instantiations, and this implementation creates a dependence of the instantiating units on the generic units as allowed by AI-00408 and AI-00506 such that the compilation of the generic bodies makes the instantiating units obsolete--no errors are detected. The processing of these tests was modified by re-compiling the obsolete units; all intended errors were then detected by the compiler.

AD7203B was graded passed by Test Modification as directed by the AVO. This implementation allocates 16K words of the target memory for task stacks; by default, equal amounts of storage are allocated to all tasks. AD7203B contains 8 tasks, in addition to the environment task; since the environment task requires in excess of 2K words, STORAGE\_ERROR is raised when the test is run. The test was modified by adding a STORAGE\_SIZE

## IMPLEMENTATION DEPENDENCIES

length clause for the task type TSK at line 165 to specify an allocation of 1024 storage units (words) for the activation of each task of the type.

CE2103A, CE2103B, and CE3107A were graded inapplicable by Evaluation Modification as directed by the AVO. The tests abort with an unhandled exception when USE\_ERROR is raised on the attempt to create an external file. This is acceptable behavior because this implementation does not support external files. (cf. AI-00332).

## CHAPTER 3

### PROCESSING INFORMATION

#### 3.1 TESTING ENVIRONMENT

The Ada implementation tested in this validation effort is described adequately by the information given in the initial pages of this report.

For technical and sales information about this Ada implementation, contact:

Uri Gries  
Aitech Defense Systems Inc.  
3080 Olcott Street, Suite 105A  
Santa Clara, CA 95054  
(408) 980-6200

Testing of this Ada implementation was conducted at the customer's site by a validation team from the AVF.

#### 3.2 SUMMARY OF TEST RESULTS

An Ada Implementation passes a given ACVC version if it processes each test of the customized test suite in accordance with the Ada Programming Language Standard, whether the test is applicable or inapplicable; otherwise, the Ada Implementation fails the ACVC [Pro90].

For all processed tests (inapplicable and applicable), a result was obtained that conforms to the Ada Programming Language Standard.

The list of items below gives the number of ACVC tests in various categories. All tests were processed, except those that were withdrawn because of test errors (item b; see section 2.1), those that require a floating-point precision that exceeds the implementation's maximum precision (item e; see section 2.2), and those that depend on the support of a file system — if none is supported (item d). All tests passed, except those that are listed in sections 2.1 and 2.2 (counted in items b and f, below).

## PROCESSING INFORMATION

|  |      |
|--|------|
| a) Total Number of Applicable Tests                | 3431 |
| b) Total Number of Withdrawn Tests                 | 95   |
| c) Processed Inapplicable Tests                    | 95   |
| d) Non-Processed I/O Tests                         | 264  |
| e) Non-Processed Floating-Point<br>Precision Tests | 285  |
| f) Total Number of Inapplicable Tests              | 644  |
| g) Total Number of Tests for ACVC 1.11             | 4170 |

### 3.3 TEST EXECUTION

A magnetic tape containing the customized test suite (see section 1.3) was taken on-site by the validation team for processing. The contents of the magnetic tape were loaded directly onto the host computer.

The tests were compiled and linked on the host computer system, as appropriate. The executable images were transferred to the target computer system through ethernet and an OPI (Once Protocol Interface) box manufactured by Aitech and run. The results were captured on the host computer system.

Testing was performed using command scripts provided by the customer and reviewed by the validation team. See Appendix B for a complete listing of the processing options for this implementation. It also indicates the default options. The options invoked explicitly for validation testing during this test were:

| Option/Switch | Effect               |
|---------------|----------------------|
| -L            | Produces list files. |
| -A            | Produces asm files.  |

Test output, compiler and linker listings, and job logs were captured on magnetic tape and archived at the AVF. The listings examined on-site by the validation team were also archived.



# APPENDIX A

## MACRO PARAMETERS

This appendix contains the macro parameters used for customizing the ACVC. The meaning and purpose of these parameters are explained in [UG89]. The parameter values are presented in two tables. The first table lists the values that are defined in terms of the maximum input-line length, which is the value for \$MAX\_IN\_LEN—also listed here. These values are expressed here as Ada string aggregates, where "V" represents the maximum input-line length.

| Macro Parameter              | Macro Value                                    |
|------------------------------|--|
| \$MAX_IN_LEN                 | 240 — Value of V                               |
| \$BIG_ID1                    | (1..V-1 => 'A', V => '1')                      |
| \$BIG_ID2                    | (1..V-1 => 'A', V => '2')                      |
| \$BIG_ID3                    | (1..V/2 => 'A') & '3' &<br>(1..V-1-V/2 => 'A') |
| \$BIG_ID4                    | (1..V/2 => 'A') & '4' &<br>(1..V-1-V/2 => 'A') |
| \$BIG_INT_LIT                | (1..V-3 => '0') & "298"                        |
| \$BIG_REAL_LIT               | (1..V-5 => '0') & "690.0"                      |
| \$BIG_STRING1                | '"' & (1..V/2 => 'A') & "'"                    |
| \$BIG_STRING2                | '"' & (1..V-1-V/2 => 'A') & '1' & "'"          |
| \$BLANKS                     | (1..V-20 => ' ')                               |
| \$MAX_LEN_INT_BASED_LITERAL  | "2:" & (1..V-5 => '0') & "11:"                 |
| \$MAX_LEN_REAL_BASED_LITERAL | "16:" & (1..V-7 => '0') & "F.E:"               |

## MACRO PARAMETERS

\$MAX\_STRING\_LITERAL    ' ' & (1..V-2 => 'A') & ' '

The following table lists all of the other macro parameters and their respective values.

| Macro Parameter                   | Macro Value                     |
|-----------------------------------|---------------------------------|
| \$ACC_SIZE                        | 32                              |
| \$ALIGNMENT                       | 1                               |
| \$COUNT_LAST                      | 2_147_483_647                   |
| \$DEFAULT_MEM_SIZE                | 32768                           |
| \$DEFAULT_STOR_UNIT               | 32                              |
| \$DEFAULT_SYS_NAME                | DSP96002                        |
| \$DELTA_DOC                       | 2#1.0#E-31                      |
| \$ENTRY_ADDRESS                   | 16#400#                         |
| \$ENTRY_ADDRESS1                  | 16#401#                         |
| \$ENTRY_ADDRESS2                  | 16#402#                         |
| \$FIELD_LAST                      | 50                              |
| \$FILE_TERMINATOR                 | ' '                             |
| \$FIXED_NAME                      | NO_SUCH_FIXED_TYPE              |
| \$FLOAT_NAME                      | NO_SUCH_TYPE                    |
| \$FORM_STRING                     | " "                             |
| \$FORM_STRING2                    | "CANNOT RESTRICT FILE CAPACITY" |
| \$GREATER_THAN_DURATION           | 75_000.0                        |
| \$GREATER_THAN_DURATION BASE LAST | I31_073.0                       |
| \$GREATER_THAN_FLOAT BASE LAST    | 1.80141E+38                     |
| \$GREATER_THAN_FLOAT_SAFE LARGE   | 1.0E38                          |

# MACRO PARAMETERS

\$GREATER\_THAN\_SHORT\_FLOAT\_SAFE\_LARGE  
 1.0E308  
  
 \$HIGH\_PRIORITY 23  
  
 \$ILLEGAL\_EXTERNAL\_FILE\_NAME1  
 \NODIRECTORY\FILENAME  
  
 \$ILLEGAL\_EXTERNAL\_FILE\_NAME2  
 THIS\_FILE\_NAME\_IS\_TOO\_LONG\_FOR\_MY\_SYSTEM  
  
 \$INAPPROPRIATE\_LINE\_LENGTH  
 -1  
  
 \$INAPPROPRIATE\_PAGE\_LENGTH  
 -1  
  
 \$INCLUDE\_PRAGMA1 PRAGMA INCLUDE ("A28006D1.ADA")  
 \$INCLUDE\_PRAGMA2 PRAGMA INCLUDE ("B28006F1.ADA")  
  
 \$INTEGER\_FIRST -2147483648  
 \$INTEGER\_LAST 2147483647  
 \$INTEGER\_LAST\_PLUS\_1 2147483648  
 \$INTERFACE\_LANGUAGE ASSEMBLER  
 \$LESS\_THAN\_DURATION -75\_000.0  
 \$LESS\_THAN\_DURATION\_BASE\_FIRST  
 -131\_073.0  
  
 \$LINE\_TERMINATOR ASCII.LF  
 \$LOW\_PRIORITY 1  
  
 \$MACHINE\_CODE\_STATEMENT  
 NULL;  
  
 \$MACHINE\_CODE\_TYPE NO\_SUCH\_TYPE  
 \$MANTISSA\_DOC 31  
 \$MAX\_DIGITS 9  
 \$MAX\_INT 2147483647  
 \$MAX\_INT\_PLUS\_1 2\_147\_483\_648  
 \$MIN\_INT -2147483648  
 \$NAME NO\_SUCH\_TYPE\_AVAILABLE

## MACRO PARAMETERS

|                       |                                     |
|-----------------------|-------------------------------------|
| \$NAME_LIST           | MC68020, MC88000, i860, DSP96002    |
| \$NAME_SPECIFICATION1 | /home/val/acvc1_11/ctest/dev/x2120a |
| \$NAME_SPECIFICATION2 | /home/val/acvc1_11/ctest/dev/x2120b |
| \$NAME_SPECIFICATION3 | /home/val/acvc1_11/ctest/dev/x2120c |
| \$NEG_BASED_INT       | 16#F000000E#                        |
| \$NEW_MEM_SIZE        | 65535                               |
| \$NEW_STOR_UNIT       | 32                                  |
| \$NEW_SYS_NAME        | MC88000                             |
| \$PAGE_TERMINATOR     | ASCII.FF                            |
| \$RECORD_DEFINITION   | NEW INTEGER;                        |
| \$RECORD_NAME         | NO_SUCH_MACHINE_CODE_TYPE           |
| \$TASK_SIZE           | 32                                  |
| \$TASK_STORAGE_SIZE   | 1024                                |
| \$TICK                | 0.000_001                           |
| \$VARIABLE_ADDRESS    | 16#0320#                            |
| \$VARIABLE_ADDRESS1   | 16#0321#                            |
| \$VARIABLE_ADDRESS2   | 16#0322#                            |
| \$YOUR_PRAGMA         | INTERFACE_PACKAGE                   |

## APPENDIX B

### COMPILATION SYSTEM OPTIONS

The compiler options of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this appendix are to compiler documentation and not to this report.

### LINKER OPTIONS

The linker options of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this appendix are to linker documentation and not to this report.

### 2.3.1 Ada Cross-Compiler (ADA96K)

The compiler is activated using the command **ADA96K**.

**Syntax:**        **ADA96K** [qualifiers]        <source-file-name>

**Parameters:** source-file-name

Denotes the file containing the source text for the compilation. If no file type is given, **.ADA** is assumed.

**Qualifiers:**    The qualifiers and options available are detailed in the following table:

| Qualifier                  | Description   | Default                  |
|----------------------------|---|--------------------------|
| <b>/asm_list</b>           | Generates an assembler file for each compilation unit. The file name is the unit name with a suffix <b>"_S"</b> or <b>"_B"</b> and the file type is <b>.ASM</b> . | <b>True</b>              |
| <b>/configuration_file</b> | Controls various parameters of the list file layout, input line length, etc.  | <b>Internal defaults</b> |
| <b>/copy_source</b>        | Saves the source file for the compilation in the library  | <b>False</b>             |
| <b>/list</b>               | Generates a list file for the compilation. The file name is that of the source file, with file type <b>.LIS</b>   | <b>False</b>             |
| <b>/library</b>            | Compiles the unit(s) into the given library   | <b>ADA96K_LIBRARY</b>    |
| <b>/optimize</b>           | Controls various optimization options   | <b>False</b>             |
| <b>/reorder</b>            | Activates the code reordering pass of the compiler  | <b>False</b>             |
| <b>/suppress_all</b>       | Disables generation of code for run-time checks   | <b>False</b>             |
| <b>/trace</b>              | Enables generation of trace-back information  | <b>False</b>             |
| <b>/verbose</b>            | Outputs information during compilation  | <b>False</b>             |
| <b>/xref</b>               | Generates a cross-reference listing in the list file  | <b>False</b>             |

### 2.3.2 Program Library Manager (PLM96K)

The interactive program library manager is activated using the command PLM96K.

**Syntax:** PLM96K [/library=<library\_name>]

**Qualifiers:** /library=<library\_name>

This optional qualifier sets the current default library for the PLM96K. If omitted, the default program library defined by the logical name ADA96K\_LIBRARY will be opened.

**Interactive Commands:** The PLM96K commands and options are detailed in the following table:

| Command | Description  | Default                          |
|---------|--|----------------------------------|
| Create  | Creates a new Ada program sublibrary or root library                                   | None                             |
| Delete  | Deletes the given unit(s) from the current default program library                     | None                             |
| Show    | Displays information for the given unit(s) from the current default program library    | None                             |
| Exit    | Leaves the program library manager   | None                             |
| Help    | Displays the PLM96K commands and options   | None                             |
| Library | Sets the current default program library for the PLM96K                                | Show the current default library |
| Type    | Displays the Ada source for the given unit(s) from the current default program library | None                             |

| Command  | Description  | Default |
|----------|--|---------|
| Extract  | Creates a copy of the stored Ada source for the given unit(s) in the current directory         | None    |
| Import   | Inserts an externally generated compilation unit body into the current default program library | None    |
| Allocate | Allocates a unit number for an externally generated compilation unit body                      | None    |
| Verify   | Checks the correctness of the current default program library                                  | None    |

### 2.3.3 Ada Cross-Linker (LNK96K)

The cross-linker is activated using the command LNK96K.

**Syntax:** LNK96K [qualifiers] <main-unit-name>

**Parameters:** main-unit-name

Denotes the main unit for the Ada program to be linked.  
The unit given must be a parameterless procedure.

**Qualifiers:** The qualifier and options available are detailed in the following table:

| Qualifier | Description  | Default        |
|-----------|--|----------------|
| /library  | Specifies the program library where the main and its required units will be looked for           | ADA96K_LIBRARY |
| /map      | Generates a map file for the link. The file name will be the main unit name, with file type .MAP | True           |



| Qualifier        | Description  | Default          |
|------------------|--|------------------|
| /progress        | Outputs information during the link process  | False            |
| /log             | Generates a log file for the link. The log file name can be given in the command. If not given, the main unit name will be used, with file type .LOG | False            |
| /directives      | Uses the directives in the given directives file to guide the link process   | None             |
| /target          | Specifies the target identifier  | 096 (ADS)        |
| /with_rts        | Includes the required modules from the RTS in the link   | False            |
| /minimal_rts     | Includes a minimal, single-task RTS in the link  | False            |
| /gen_rts         | Generates the load file for a new fully-configured RTS executable image  | False            |
| /trace           | Enables the RTS tracing functions  | False            |
| /first_address   | Specifies the initial memory addresses for X, Y and P spaces   | (800,800,400)    |
| /last_address    | Specifies the last memory addresses for X, Y, and P spaces   | (7FFE,7FFE,FFFE) |
| /rts_size        | Specifies the maximal size of a fully-configured RTS in the different memory spaces  | (800,200,3C00)   |
| /external_module | Includes the given object file(s) or modules from the given object library in the link   | None             |
| /flags           | Controls various special functions of the linker   | None             |

## APPENDIX C

### APPENDIX F OF THE Ada STANDARD

The only allowed implementation dependencies correspond to implementation-dependent pragmas, to certain machine-dependent conventions as mentioned in Chapter 13 of the Ada Standard, and to certain allowed restrictions on representation clauses. The implementation-dependent characteristics of this Ada implementation, as described in this Appendix, are provided by the customer. Unless specifically noted otherwise, references in this Appendix are to compiler documentation and not to this report. Implementation-specific portions of the package STANDARD, which are not a part of Appendix F, are:

package STANDARD is

.....

type INTEGER is range -2147483648 .. 2147483647;

type FLOAT is digits 6 range -3.40282E+38 .. 3.40282E+38;

type LONG\_FLOAT is digits 9 range  
-1.79769313E+308 .. 1.79769313E+308;

type DURATION is delta 2\*\* -14 range -131072.0 .. 131072.0;

.....

end STANDARD;

## **Appendix F of the Ada Reference Manual**

This appendix describes the implementation-dependent characteristics of the AI-ADA/96K Cross-Compilation System, as required in the Appendix F frame of the Ada Reference Manual (ANSI/MIL-STD-1815A).

### **B.1 Implementation-Dependent Pragmas**

The following implementation-dependent pragmas are defined in the compiler:

- `suppress_all`
- `interface_package`
- `external_subprogram_name`

For detailed information on the use of these pragmas, refer to Section 6.8, "Implementation-Dependent Features."

### **B.2 Implementation-Dependent Attributes**

No implementation-dependent attributes are defined for this version.

### **B.3 Package SYSTEM**

The specification of the package SYSTEM:

```
package SYSTEM is
  type ADDRESS is new INTEGER;
  type PRIORITY is range 1 .. 23;
    -- Priority 0 is reserved for the Null Task
    -- Priority 24 is reserved for System Tasks
    -- Priorities 25..31 are for interrupts
  type NAME is (MC68020, MC88000, i860, DSP96002);
  SYSTEM_NAME: constant NAME := DSP96002;
  STORAGE_UNIT: constant := 32;
  MEMORY_SIZE: constant := 32 * 1024;
  MIN_INT: constant := -2_147_483_647-1;
  MAX_INT: constant := 2_147_483_647;
  MAX_DIGITS: constant := 9;
  MAX_MANTISSA: constant := 31;
```

```
FINE_DELTA:  constant      := 2.0 ** (-31);  
TICK:        constant      := 0.000_001;  
  
type INTERFACE_LANGUAGE is (ASSEMBLER,C,RTS) ;  
  
end SYSTEM;
```

## **B.4. Representation Clauses**

### **B.4.1 Length Clauses**

The following kinds of length clauses are supported:

1. Size specification: **T'size**

Supported as described in ARM. For scalar objects residing in the frame, the smallest possible size (in complete words) will always be chosen by the compiler.

2. Specification of a collection size: **T'storage\_size**

Specifies the number of storage units allocated to the collection associated with access type T.

3. Specification of task size: **T'storage\_size**

Specifies the number of storage units allocated for each activation of a task of type T. This size includes space for the task's stack, as well as some RTS overhead (approximately 54 words).

4. Specification of small for a fixed point type: **T'small**

### **B.4.2 Enumeration Representation Clause**

Enumeration representation clauses may specify representations in the range of the predefined type INTEGER.

### **B.4.3. Record Representation Clause**

Record representation clauses are supported as detailed in Section 13.4 of the ARM.

### **B.5 Implementation-Dependent Names for Implementation-Dependent Components**

None defined by the compiler.

### **B.6 Address Clauses**

Address clauses are supported for objects (variables or constants) and task entries (linkage to hardware interrupt); refer to Chapter 16, "AI-TCK Target Configuration Kit."

Address clauses for objects are interpreted as absolute addresses, and code is generated using the ORG directive. The compiler does not check for possible overlaps.

### **B.7. Unchecked Conversion**

No warning is issued when conversion between objects of different sizes is performed. The result of such a conversion is unpredictable.

### **B.8. Input-Output Packages**

Input-Output packages are supplied with the AI-ADA/96K Cross-Compiler System.

Standard\_input and Standard\_output are supported. External files and file objects are implementation dependent, and therefore are handled as specified in the ARM.

**B.8.1. Specification of the Package Sequential\_IO**

```
with BASIC_IO_TYPES;
with IO_EXCEPTIONS;
generic
  type ELEMENT_TYPE is private;
package SEQUENTIAL_IO is
  type FILE_TYPE is limited private;
  type FILE_MODE is (IN_FILE, OUT_FILE);

  -- File management
  procedure CREATE (
    FILE : in out FILE_TYPE;
    MODE : in FILE_MODE := OUT_FILE;
    NAME : in STRING := ""; FORM : in STRING := "");

  procedure OPEN (
    FILE : in out FILE_TYPE;
    MODE : in FILE_MODE;
    NAME : in STRING;
    FORM : in STRING := "");

  procedure CLOSE (FILE : in out FILE_TYPE);
  procedure DELETE (FILE : in out FILE_TYPE);
  procedure RESET (
    FILE : in out FILE_TYPE;
    MODE : in FILE_MODE);

  procedure RESET (FILE : in out FILE_TYPE);
  function MODE (FILE : in FILE_TYPE) return FILE_MODE;
  function NAME (FILE : in FILE_TYPE) return STRING;

  function FORM (FILE : in FILE_TYPE) return STRING;
  function IS_OPEN(FILE : in FILE_TYPE) return BOOLEAN;
  -- input and output operations
  procedure READ (
    FILE : in FILE_TYPE;
    ITEM : out ELEMENT_TYPE);

  procedure WRITE (
    FILE : in FILE_TYPE;
    ITEM : in ELEMENT_TYPE);
  function END_OF_FILE (FILE : in FILE_TYPE)
    return BOOLEAN;
```

```
-- exceptions
STATUS_ERROR : exception renames
  IO_EXCEPTIONS.STATUS_ERROR;
MODE_ERROR   : exception renames
  IO_EXCEPTIONS.MODE_ERROR;
NAME_ERROR   : exception renames
  IO_EXCEPTIONS.NAME_ERROR;
USE_ERROR    : exception renames
  IO_EXCEPTIONS.USE_ERROR;
DEVICE_ERROR : exception renames
  IO_EXCEPTIONS.DEVICE_ERROR;
END_ERROR    : exception renames
  IO_EXCEPTIONS.END_ERROR;
DATA_ERROR   : exception renames
  IO_EXCEPTIONS.DATA_ERROR;

private
  type FILE_TYPE is new BASIC_IO_TYPES.FILE_TYPE;

end SEQUENTIAL_IO;
```

## B.8.2 Specification for Package Direct Input-Output

```
with BASIC_IO_TYPES;
with IO_EXCEPTIONS;
generic
  type ELEMENT_TYPE is private;
package DIRECT_IO is
  type FILE_TYPE is limited private;
  type FILE_MODE is (IN_FILE, INOUT_FILE, OUT_FILE);
  type COUNT is range 0..INTEGER'LAST;
  subtype POSITIVE_COUNT is COUNT range 1..COUNT'LAST;
  -- File management

  procedure CREATE (
    FILE : in out FILE_TYPE;
    MODE : in FILE_MODE := INOUT_FILE;
    NAME : in STRING := "";
    FORM : in STRING := "");

  procedure OPEN (
    FILE : in out FILE_TYPE;
    MODE : in FILE_MODE;
    NAME : in STRING;
    FORM : in STRING := "");

  procedure CLOSE (FILE : in out FILE_TYPE);
  procedure DELETE (FILE : in out FILE_TYPE);
  procedure RESET (
```

```
FILE : in out FILE_TYPE;
MODE : in FILE_MODE);

procedure RESET (FILE : in out FILE_TYPE);
function MODE (FILE : in FILE_TYPE) return FILE_MODE;
function NAME (FILE : in FILE_TYPE) return STRING;
function FORM (FILE : in FILE_TYPE) return STRING;
function IS_OPEN(FILE : in FILE_TYPE) return BOOLEAN;

-- input and output operations

procedure READ (
  FILE : in FILE_TYPE;
  ITEM : out ELEMENT_TYPE;
  FROM : in POSITIVE_COUNT);

procedure READ (
  FILE : in FILE_TYPE;
  ITEM : out ELEMENT_TYPE);

procedure WRITE (
  FILE : in FILE_TYPE;
  ITEM : in ELEMENT_TYPE;
  TO : in POSITIVE_COUNT);

procedure WRITE (
  FILE : in FILE_TYPE;
  ITEM : in ELEMENT_TYPE);

procedure SET INDEX(
  FILE : in FILE_TYPE;
  TO : in POSITIVE_COUNT);

function INDEX( FILE : in FILE_TYPE) return
  POSITIVE_COUNT;

function SIZE (FILE : in FILE_TYPE) return COUNT;
function END OF FILE(FILE : in FILE_TYPE)
  return BOOLEAN;

-- exceptions

STATUS_ERROR : exception renames
  IO_EXCEPTIONS.STATUS_ERROR;
MODE_ERROR : exception renames
  IO_EXCEPTIONS.MODE_ERROR;
NAME_ERROR : exception renames
  IO_EXCEPTIONS.NAME_ERROR;
USE_ERROR : exception renames
  IO_EXCEPTIONS.USE_ERROR;
```



```

DEVICE_ERROR : exception renames
  IO_EXCEPTIONS.DEVICE_ERROR;
END_ERROR    : exception renames
  IO_EXCEPTIONS.END_ERROR;
DATA_ERROR   : exception renames
  IO_EXCEPTIONS.DATA_ERROR;

private
  type FILE_TYPE is new BASIC_IO_TYPES.FILE_TYPE;

end DIRECT_IO;

```

### B.8.3. Specification of Package Text Input-Output

```

with BASIC_IO_TYPES;
with IO_EXCEPTIONS;
package TEXT_IO is
  type FILE_TYPE is limited private;
  type FILE_MODE is (IN_FILE, OUT_FILE);
  type COUNT is range 0 .. INTEGER'LAST;
  subtype POSITIVE_COUNT is COUNT range 1 .. COUNT'LAST;

  UNBOUNDED: constant COUNT := 0; -- line and page length
  subtype FIELD is INTEGER range 0 .. 35;
  subtype NUMBER_BASE is INTEGER range 2 .. 16;
  type TYPE_SET is (LOWER_CASE, UPPER_CASE);

  -- File Management

  procedure CREATE (
    FILE : in out FILE_TYPE;
    MODE : in FILE_MODE := OUT_FILE;
    NAME : in STRING    := "";
    FORM : in STRING    := "");

  procedure OPEN (
    FILE : in out FILE_TYPE;
    MODE : in FILE_MODE;
    NAME : in STRING;
    FORM : in STRING    := "");

  procedure CLOSE (FILE : in out FILE_TYPE);
  procedure DELETE (FILE : in out FILE_TYPE);
  procedure RESET (
    FILE : in out FILE_TYPE;
    MODE : in FILE_MODE);

```

```

procedure RESET (FILE : in out FILE_TYPE);
function MODE (FILE : in FILE_TYPE) return
    FILE_MODE;
function NAME (FILE : in FILE_TYPE) return STRING;
function FORM (FILE : in FILE_TYPE) return STRING;
function IS_OPEN (FILE : in FILE_TYPE) return BOOLEAN;

-- Control of default input and output files

procedure SET_INPUT (FILE : in FILE_TYPE);
procedure SET_OUTPUT (FILE : in FILE_TYPE);
function STANDARD_INPUT return FILE_TYPE;
function STANDARD_OUTPUT return FILE_TYPE;
function CURRENT_INPUT return FILE_TYPE;
function CURRENT_OUTPUT return FILE_TYPE;

-- specification of line and page lengths

procedure SET_LINE_LENGTH (
    FILE : in FILE_TYPE;
    TO : in COUNT);

procedure SET_LINE_LENGTH (TO : in COUNT);
procedure SET_PAGE_LENGTH (
    FILE : in FILE_TYPE;
    TO : in COUNT);

procedure SET_PAGE_LENGTH (TO : in COUNT);
function LINE_LENGTH (FILE : in FILE_TYPE)
    return COUNT;
function LINE_LENGTH return COUNT;
function PAGE_LENGTH (FILE : in FILE_TYPE)
    return COUNT;
function PAGE_LENGTH return COUNT;

-- Column, Line, and Page Control

procedure NEW_LINE (
    FILE : in FILE_TYPE;
    SPACING : in POSITIVE_COUNT := 1);

procedure NEW_LINE (SPACING : in POSITIVE_COUNT := 1);

procedure SKIP_LINE (
    FILE : in FILE_TYPE;
    SPACING : in POSITIVE_COUNT := 1);

procedure SKIP_LINE (SPACING : in POSITIVE_COUNT
    := 1);

function END_OF_LINE (FILE : in FILE_TYPE)
    return BOOLEAN;

```

```

function END_OF_LINE return BOOLEAN;

procedure NEW_PAGE (FILE : in FILE_TYPE);
procedure NEW_PAGE ;

procedure SKIP_PAGE (FILE : in FILE_TYPE);
procedure SKIP_PAGE ;

function END_OF_PAGE (FILE : in FILE_TYPE)
return BOOLEAN;
function END_OF_PAGE return BOOLEAN;

function END_OF_FILE (FILE : in FILE_TYPE)
return BOOLEAN;
function END_OF_FILE return BOOLEAN;

procedure SET_COL (FILE : in FILE_TYPE;
(TO : in POSITIVE_COUNT);

procedure SET_COL (TO : in POSITIVE_COUNT);
procedure SET_LINE (FILE : in FILE_TYPE;
(TO : in POSITIVE_COUNT);

procedure SET_LINE (TO : in POSITIVE_COUNT);
function COL (FILE : in FILE_TYPE)
return POSITIVE_COUNT;
function COL return POSITIVE_COUNT;

function LINE (FILE : in FILE_TYPE)
return POSITIVE_COUNT;
function LINE return POSITIVE_COUNT;

function PAGE (FILE : in FILE_TYPE)
return POSITIVE_COUNT;
function PAGE return POSITIVE_COUNT;

-- Character Input-Output

procedure GET (
FILE : in FILE_TYPE;
ITEM : out CHARACTER);

procedure GET (ITEM : out CHARACTER);

procedure PUT (
FILE : in FILE_TYPE;
ITEM : in CHARACTER);
procedure PUT (ITEM : in CHARACTER);

```

-- String Input-Output

```
procedure GET (
  FILE : in FILE_TYPE;
  ITEM : out STRING);
```

```
procedure GET (ITEM : out STRING);
```

```
procedure PUT (
  FILE : in FILE_TYPE;
  ITEM : in STRING);
```

```
procedure PUT (ITEM : in STRING);
```

```
procedure GET_LINE (
  FILE : in FILE_TYPE;
  ITEM : out STRING;
  LAST : out NATURAL);
```

```
procedure GET_LINE (
  ITEM : out STRING;
  LAST : out NATURAL);
```

```
procedure PUT_LINE (
  FILE : in FILE_TYPE;
  ITEM : in STRING);
```

```
procedure PUT_LINE (ITEM : in STRING);
```

-- Generic Package for Input-Output of Integer Types

generic

```
type NUM is range <>;
```

```
package INTEGER_IO is
  DEFAULT_WIDTH : FIELD := NUM'WIDTH;
  DEFAULT_BASE  : NUMBER_BASE := 10;
```

```
procedure GET (
  FILE : in FILE_TYPE;
  ITEM : out NUM;
  WIDTH : in FIELD := 0);
```

```
procedure GET (
  ITEM : out NUM;
  WIDTH : in FIELD := 0);
```

```

procedure PUT (
  FILE : in FILE_TYPE;
  ITEM  : in NUM;
  WIDTH : in FIELD := DEFAULT_WIDTH;
  BASE  : in NUMBER_BASE := DEFAULT_BASE);

procedure PUT (
  ITEM  : in NUM;
  WIDTH : in FIELD := DEFAULT_WIDTH;
  BASE  : in NUMBER_BASE := DEFAULT_BASE);

procedure GET (
  FROM : in STRING;
  ITEM  : out NUM;
  LAST  : out POSITIVE);

procedure PUT (
  TO      : out STRING;
  ITEM    : in NUM;
  BASE    : in NUMBER_BASE := DEFAULT_BASE);

end INTEGER_IO;

-- Generic Packages for Input-Output of Real Types

generic

  type NUM is digits <>;
  package FLOAT_IO is

    DEFAULT_FORE : FIELD := 2;
    DEFAULT_AFT  : FIELD := NUM'digits - 1;
    DEFAULT_EXP  : FIELD := 3;

    procedure GET (
      FILE : in FILE_TYPE;
      ITEM  : out NUM;
      WIDTH : in FIELD := 0);

    procedure GET (
      ITEM  : out NUM;
      WIDTH : in FIELD := 0);

    procedure PUT (
      FILE : in FILE_TYPE;
      ITEM  : in NUM;
      FORE  : in FIELD := DEFAULT_FORE;
      AFT   : in FIELD := DEFAULT_AFT;
      EXP   : in FIELD := DEFAULT_EXP);
  end package;

```

```

procedure PUT (
  ITEM : in NUM;
  FORE : in FIELD := DEFAULT_FORE;
  AFT  : in FIELD := DEFAULT_AFT;
  EXP  : in FIELD := DEFAULT_EXP);

procedure GET (
  FROM : in STRING;
  ITEM : out NUM;
  LAST : out POSITIVE);

procedure PUT (TO : out STRING;
  ITEM : in NUM;
  AFT  : in FIELD := DEFAULT_AFT;
  EXP  : in FIELD := DEFAULT_EXP);

end FLOAT_IO;

generic
type NUM is delta <>;
package FIXED_IO is

  DEFAULT_FORE : FIELD := NUM'FORE;
  DEFAULT_AFT  : FIELD := NUM'AFT;
  DEFAULT_EXP  : FIELD := 0;
  procedure GET (FILE : in FILE_TYPE;
    ITEM : out NUM;
    WIDTH : in FIELD := 0);

  procedure GET (
    ITEM : out NUM;
    WIDTH : in FIELD := 0);

  procedure PUT (
    FILE : in FILE_TYPE;
    ITEM : in NUM;
    FORE : in FIELD := DEFAULT_FORE;
    AFT  : in FIELD := DEFAULT_AFT;
    EXP  : in FIELD := DEFAULT_EXP);

  procedure PUT (ITEM : in NUM;
    FORE : in FIELD := DEFAULT_FORE;
    AFT  : in FIELD := DEFAULT_AFT;
    EXP  : in FIELD := DEFAULT_EXP);

  procedure GET (
    FROM : in STRING;
    ITEM : out NUM;
    LAST : out POSITIVE);

```

```

procedure PUT (
    TO : out STRING;
    ITEM : in NUM;
    AFT : in FIELD := DEFAULT_AFT;
    EXP : in FIELD := DEFAULT_EXP);

end FIXED_IO;

-- Generic package for Input-Output of Enumeration
Types

generic

type ENUM is (<>);
package ENUMERATION_IO is
    DEFAULT_WIDTH : FIELD := 0;
    DEFAULT_SETTING : TYPE_SET := UPPER_CASE;
    procedure GET (
        FILE : in FILE_TYPE;
        ITEM : out ENUM);

    procedure GET (ITEM : out ENUM);
    procedure PUT (
        FILE : in FILE_TYPE;
        ITEM : in ENUM;
        WIDTH : in FIELD := DEFAULT_WIDTH;
        SET : in TYPE_SET := DEFAULT_SETTING);

    procedure PUT (
        ITEM : in ENUM;
        WIDTH : in FIELD := DEFAULT_WIDTH;
        SET : in TYPE_SET := DEFAULT_SETTING);

    procedure GET (FROM : in STRING;
        ITEM : out ENUM;
        LAST : out POSITIVE);

    procedure PUT (TO : out STRING;
        ITEM : in ENUM;
        SET : in TYPE_SET := DEFAULT_SETTING);

end ENUMERATION_IO;

```

**-- Exceptions**

```
STATUS_ERROR : exception renames
  IO_EXCEPTIONS.STATUS_ERROR;
MODE_ERROR   : exception renames
  IO_EXCEPTIONS.MODE_ERROR;
NAME_ERROR   : exception renames
  IO_EXCEPTIONS.NAME_ERROR;
USE_ERROR    : exception renames
  IO_EXCEPTIONS.USE_ERROR;
DEVICE_ERROR : exception renames
  IO_EXCEPTIONS.DEVICE_ERROR;
END_ERROR    : exception renames
  IO_EXCEPTIONS.END_ERROR;
DATA_ERROR   : exception renames
  IO_EXCEPTIONS.DATA_ERROR;
LAYOUT_ERROR : exception renames
  IO_EXCEPTIONS.LAYOUT_ERROR;
```

**private**

```
type FILE_TYPE is new BASIC_IO_TYPES.FILE_TYPE;
and TEXT_IO;
```